Amendments to the Claims:

extend; and

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An electro-optical device, comprising: a substrate; data lines; scanning lines extending in a direction crossing the data lines; switching elements to which a scanning signal is supplied through the scanning lines; pixel electrodes to which an image signal is supplied through the data lines and the switching elements; and an alignment film formed on the pixel electrodes; the substrate having an image display area defined as an area to form the pixel electrodes and the switching elements, and a peripheral area defining the periphery of the image display area, the alignment film being formed in the image display area and the peripheral area, and convex portions being formed in the alignment film at least at a part of the peripheral area and extending in a direction substantially perpendicular to a rubbing direction of the alignment film; projected portions caused by the height of at least one of the data lines and the scanning lines being formed in the alignment film at a position directly adjacent to the display area, the convex portions being formed along a direction in which the scanning lines or the data lines extend and the convex portions including a plurality of linear convex portions which are formed along the direction in which the scanning lines or the data lines

the pitch between the linear convex portions being equal to the pitch between the projected portions.

- 2. (Original) The electro-optical device according to Claim 1, further comprising a driving circuit on the substrate, the convex portions being provided in an area between the image display area and the driving circuit.
- 3. (Original) The electro-optical device according to Claim 1, further including a dummy pixel forming area formed outside the image display area, the convex portions being formed outside the dummy pixel forming area.
- 4. (Previously Presented) The electro-optical device according to Claim 1, projected portions caused by the height of at least one of the data lines and the scanning lines being formed in the alignment film at a position directly adjacent to the display area, and the height of the convex portions being equal to the height of the projected portions.
 - 5. (Canceled).
- 6. (Currently Amended) The electro-optical device according to Claim 5, Claim 1, the convex portions being formed parallel to the direction in which the scanning lines or the data lines extend.
 - 7-8. (Canceled)
- 9. (Currently Amended) The electro-optical device according to Claim 7, An electro-optical device, comprising:

 a substrate;

 data lines;

 scanning lines extending in a direction crossing the data lines;

scanning lines;

switching elements to which a scanning signal is supplied through the

pixel electrodes to which an image signal is supplied through the data lines
and the switching elements;
an alignment film formed on the pixel electrodes;
the substrate having an image display area defined as an area to form the pixel
electrodes and the switching elements, and a peripheral area defining the periphery of the
image display area, the alignment film being formed in the image display area and the
peripheral area, and convex portions being formed in the alignment film at least at a part of
the peripheral area and extending in a direction substantially perpendicular to a rubbing
direction of the alignment film;
projected portions caused by the height of at least one of the data lines and the
scanning lines being formed in the alignment film at a position directly adjacent to the display
area,
the convex portions being formed along a direction in which the scanning lines
or the data lines extend, and the convex portions including a plurality of linear convex
portions which are formed along the direction in which the scanning lines or the data lines
extend; and
the pitch between the linear convex portions being gradually increased or
decreased with increasing distance from the image display area, from a place close to the
image display area to a place apart from the image display area.
10. (Original) The electro-optical device according to Claim 1, the convex
portions being formed along the peripheral portion of the image display area opposite to the

11. (Original) The electro-optical device according to Claim 1, the substrate having a rectangular outer configuration in plan view, and the image display area having a shape similar to the outer configuration of the substrate, and

direction of a rubbing process performed on the alignment film.

the convex portions being formed along one side or two adjacent sides of the image display area.

- 12. (Original) The electro-optical device according to Claim 1, the convex portions being caused by the height of a pattern formed of the same film as the data lines, the scanning lines, or the switching elements.
 - 13. (Original) An electronic apparatus, comprising: the electro-optical device according to Claim 1.